

Base Line: Hydraulic Guillotine Shears

Model Number	Max Cutting Thickness	Max Cutting Length	Shear Angle	Strokes/Minute	Backgauge Retract Dist	Nominal Motor Power	Machine Dimensions	Machine Weight
SMO-3212-E21	1/2 in (12 mm)	122 in	2°	9	23 in	15 kW	14 x 7 x 7 ft	20948 lb
SMO-4012-E21	1/2 in (12 mm)	158 in	2°	8	23 in	18.5 kW	16 x 7 x 7 ft	27562 lb
SMO-2506-E21	1/4 in (6 mm)	98 in	0.5° - 2.5°	18	23 in	7.5 kW	11 x 6 x 7 ft	8379 lb
SMO-3206-E21	1/4 in (6 mm)	122 in	1.5°	14	23 in	7.5 kW	13 x 6 x 6 ft	11466 lb
SMO-4006-E21	1/4 in (6 mm)	158 in	1.5°	14	23 in	7.5 kW	16 x 6 x 7 ft	15876 lb
SMO-2004-E21	1/6 in (4 mm)	63 in	0.5° - 1.5°	6 - 20	23 in	4 kW	9 x 5 x 6 ft	5512 lb
SMO-2504-E21	1/6 in (4 mm)	98 in	1.5°	6 - 12	23 in	5.5 kW	11 x 5 x 6 ft	4056 lb
SMO-3204-E21	1/6 in (4 mm)	122 in	1.5°	8 - 12	23 in	5.5 kW	13 x 6 x 6 ft	9261 lb
SMO-4004-E21	1/6 in (4 mm)	158 in	1.5°	12	23 in	5.5 kW	16 x 7 x 6 ft	14322 lb
SMO-2510-E21	3/8 in (10 mm)	98 in	1.5°	10	23 in	11 kW	11 x 6 x 7 ft	13892 lb
SMO-3210-E21	3/8 in (10 mm)	122 in	1.5°	10 - 12	23 in	15 kW	14 x 6 x 7 ft	18522 lb
SMO-4010-E21	3/8 in (10 mm)	158 in	1.5°	8	23 in	15 kW	16 x 6 x 7 ft	22491 lb
SMO-2508-E21	1/3 in (8 mm)	98 in	1.5°	14	23 in	7.5 kW	11 x 6 x 7 ft	10584 lb
SMO-3208-E21	1/3 in (8 mm)	122 in	1.5°	10 - 15	23 in	11 kW	15 x 7 x 7 ft	14112 lb
SMO-4008-E21	1/3 in (8 mm)	158 in	1.5°	8	23 in	11 kW	16 x 6 x 7 ft	16096 lb

E21S Controller (Mounted on a swivel arm on the left-hand side of the machine)

- Controllable backgauge
- Ability to store up to 40 programs, with each program accommodating up to 25 individual steps.
- Retract function
- Saving parameters with a single click
- Parameter memory backup in case of power cut



**UNIVERSAL
TUBE & ROLLFORM
EQUIPMENT CO.**
A UCG COMPANY

+1 (419) 872-2364

sales@utubeonline.com