

Pro Line: Press Brake

Model Number	Bending Capacity	Max Working Length	Throat Depth	Max Ram Stroke	Daylight	Dist Btwn Side Frames	Backgauge Retract Dist	Nominal Motor Power
PBE-1204	44 Ton	50 in	11 in	8 in	16 in	4 ft	29 in	2 kW
PBO-2160	66 Ton	82 in	16 in	12 in	18 in	9 ft	29 in	11 kW
PBO-2106	66 Ton	83 in	16 in	8 in	19 in	6 ft	29 in	5.5 kW
PBO-2609	99 Ton	102 in	16 in	10 in	21 in	7 ft	29 in	7.5 kW
PBO-3109	99 Ton	122 in	16 in	10 in	21 in	9 ft	29 in	7.5 kW
PBO-3112	132 Ton	122 in	16 in	12 in	18 in	9 ft	29 in	11 kW
PBO-3116	176 Ton	122 in	16 in	12 in	18 in	12 ft	29 in	18.5 kW
PBO-4116	176 Ton	162 in	16 in	10 in	21 in	12 ft	29 in	15 kW
PBO-3717	178 Ton	145 in	16 in	12 in	18 in	11 ft	29 in	15 kW
PBO-3722	193 Ton	145 in	16 in	12 in	18 in	11 ft	29 in	15 kW
PBO-3120	220 Ton	122 in	16 in	10 in	21 in	9 ft	29 in	19 kW
PBO-4120	220 Ton	161 in	16 in	12 in	18 in	12 ft	29 in	22 kW
PBO-3124	264 Ton	122 in	16 in	10 in	21 in	9 ft	29 in	22 kW
PBO-4124	264 Ton	161 in	16 in	12 in	18 in	12 ft	29 in	22 kW

Delem DA-58T controller

- Single-click program generation
- Advanced operator guidance based on algorithms
- Advanced, graphic simulation of bending sequences
- Operator prompts included
- Algorithms to shorten the production process
- Automatic crowning
- High-resolution TFT touch screen
- USB interface

Delem DA-66T

- Automatic control of 8 axes translating into more efficient bending
- Storing up to 500 programs, each consisting of 25 steps and 99 repetitions
- Saving up to 30 upper and lower dies
- Controller with 2D/3D programing mode
- 17" TFT touch screen
- Windows with controller software (possibility to create programs on the PC)
- Crowning control managed through the controller.
- Complex Delem design
- USB that allows connecting in new devices
- Available space for connecting a bending angle sensor
- Controls and sensors prevent collisions along individual axes.

Delem DA-69T

- 2D and 3D graphical touch programming module
- 3D visualization for simulation and processing
- 17" colour TFT screen of high resolution
- Full Windows operating system
- Compatibility with Modusys Delem system
- External USB port
- Detailed user support in a multitasking environment
- Bending using the sensors in parameter adjustment menu
- Profile-T3D offline software



+1 (419) 872-2364
sales@utubeonline.com