

Pro Line: Hydraulic Guillotine Shears

Model Number	Cutting Thickness	Max Cutting Length	Rake Angle	Strokes Per Minute	Number of Holddowns	Motor Power	Oil Tank Capacity	Machine Weight
SMO-2106-PRO	1/4 in (6 mm) ≤ 450 N/mm ²	83 in	1.6°	26	13 pcs	11 kW	42 gal	8820 lb
	1/6 in (4 mm) ≤ 750 N/mm ²							
SMO-2606-PRO	1/4 in (6 mm) ≤ 450 N/mm ²	102 in	1.6°	24	15 pcs	11 kW	42 gal	10364 lb
	1/6 in (4 mm) ≤ 750 N/mm ²							
SMO-3106-PRO	1/4 in (6 mm) ≤ 450 N/mm ²	122 in	1.6°	30	17 pcs	11 kW	42 gal	12128 lb
	1/6 in (4 mm) ≤ 750 N/mm ²							
SMO-3108-PRO	5/16 in (8 mm) ≤ 450 N/mm ²	122 in	1.8°	13	17 pcs	15 kW	42 gal	14222 lb
	13/64 in (5 mm) ≤ 750 N/mm ²							

Controller CybTouch 8w (Mounted on a swivel arm on the left-hand side of the machine)

- Automatic calculations of the shear functions upon material specifications.
- Automatic blade gap.
- Automatic back gauge correction.
- Automatic back gauge foldaway.
- 2/3- position sheet support.
- Return to sender function (RTS).
- Front or back gauge management.
- Parking position (foldaway function).
- Hold-downs pressure management.
- System pressure management.
- Large cutting sequences and programs can be memorized.vivid colors.
- Simple pages, large keys, clear display with all the information the operator needs.
- Intuitive and user-friendly interface.
- Complete programming of parts in seconds.



UT UNIVERSAL
TUBE & ROLLFORM
EQUIPMENT CO.
A UCG COMPANY

+1 (419) 872-2364
sales@utubeonline.com