

Pro Line: Press Brake

Model Number	Bending Capacity	Max Working Length	Throat Depth	Max Ram Stroke	Daylight	Dist Btwn Side Frames	Nominal Motor Power	Controller	Machine Dimensions	Machine Weight
PBO-2160-CNC	66 Ton	82 in	16 in	12 in	18 in	9 ft	4 kW	Delem DA-66T	16 x 8 x 10 ft	17089 lb
PBO-3112-CNC	132 Ton	122 in	16 in	12 in	18 in	9 ft	11 kW	Delem DA-66T	16 x 8 x 10 ft	19514 lb
PBO-3116-CNC	176 Ton	122 in	16 in	12 in	18 in	12 ft	18.5 kW	Delem DA-66T	19 x 9 x 10 ft	28114 lb
PBO-4120-CNC	220 Ton	161 in	16 in	12 in	18 in	12 ft	22 kW	Delem DA-66T	19 x 9 x 10 ft	31532 lb
PBO-4124-CNC	264 Ton	161 in	16 in	12 in	18 in	12 ft	22 kW	Delem DA-66T	19 x 9 x 10 ft	31532 lb
PBO-3717-CNC	178 Ton	145 in	16 in	12 in	18 in	11 ft	15 kW	Delem DA-66T	18 x 8 x 10 ft	23152 lb
PBO-3722-DA66	193 Ton	145 in	16 in	12 in	18 in	11 ft	15 kW	Delem DA-66T	18 x 8 x 10 ft	26350 lb
PBO-3722-DA69	242 Ton	145 in	20 in	16 in	24 in	11 ft	18.5 kW	Delem DA-69T	20 x 10 x 11 ft	29988 lb
PBE-1204-DA58	44 Ton	50 in	11 in	8 in	16 in	4 ft	2 kW	Delem DA-58T	7 x 5 x 9 ft	8820 lb
PBO-1204-PRO	44 Ton	50 in	16 in	8 in	18 in	4 ft	4 kW	Delem DA-66T	7 x 5 x 9 ft	7276 lb
PBO-3109-PRO	99 Ton	122 in	16 in	10 in	21 in	9 ft	7.5 kW	Delem DA-66T	12 x 9 x 10 ft	17420 lb
PBO-3112-PRO	132 Ton	122 in	16 in	10 in	21 in	9 ft	11 kW	Delem DA-66T	12 x 9 x 10 ft	18522 lb
PBO-3116-PRO	176 Ton	122 in	16 in	10 in	21 in	9 ft	15 kW	Delem DA-66T	12 x 9 x 10 ft	21388 lb
PBO-4116-PRO	176 Ton	162 in	16 in	10 in	21 in	12 ft	15 kW	Delem DA-66T	19 x 9 x 10 ft	26460 lb
PBO-3722-DA66	193 Ton	145 in	16 in	12 in	18 in	11 ft	15 kW	Delem DA-66T	18 x 8 x 10 ft	26350 lb
PBO-3120-PRO	220 Ton	122 in	16 in	10 in	21 in	9 ft	19 kW	Delem DA-66T	12 x 9 x 10 ft	22050 lb
PBO-4120-PRO	220 Ton	162 in	16 in	10 in	21 in	12 ft	18.5 kW	Delem DA-66T	19 x 9 x 10 ft	27562 lb
PBO-3722-DA69	242 Ton	145 in	20 in	16 in	24 in	11 ft	18.5 kW	Delem DA-69T	20 x 10 x 11 ft	29988 lb
PBO-3124-PRO	264 Ton	122 in	16 in	10 in	21 in	9 ft	22 kW	Delem DA-66T	12 x 9 x 10 ft	24255 lb
PBO-4124-PRO	264 Ton	162 in	16 in	10 in	21 in	12 ft	22 kW	Delem DA-66T	19 x 9 x 10 ft	30870 lb

Delem DA-66T controller

- Automatic control of 8 axes translating into more efficient bending
- Storing up to 500 programs, each consisting of 25 steps and 99 repetitions
- Saving up to 30 upper and lower dies
- Controller with 2D/3D programing mode
- 17" TFT touch screen
- Windows with controller software (possibility to create programs on the PC)
- Crownng control managed through the controller.
- Complex Delem design
- USB that allows connecting in new devices
- Available space for connecting a bending angle sensor
- Controls and sensors prevent collisions along individual axes.



UNIVERSAL TUBE & ROLLFORM EQUIPMENT co.
A UCG COMPANY

+1 (419) 872-2364

sales@utubeonline.com

Delem DA-69T controller

- 2D and 3D graphical touch programming module
- 3D visualization for simulation and processing
- 17" colour TFT screen of high resolution
- Full Windows operating system
- Compatibility with the Modusys Delem system (modular scalability and adaptability)
- External USB port
- Detailed user support in a multitasking environment
- Bending using the sensors in parameter adjustment menu
- Profile-T3D offline software