

Laser Tube Cutting Machine

Model Number	Max Section Height	Max Section Length	Max Thickness Mild Steel	Max Thickness Stainless Steel	Max Thickness Aluminum	Max Thickness Brass	Laser Power Output
FLT-6012-1000W	4 in	20 ft	10 mm	5 mm	3 mm	3 mm	1 kW
FLT-6012-1500W	4 in	20 ft	22 mm	10 mm	8 mm	6 mm	1.5 kW
FLT-6012-2000W	4 in	20 ft	22 mm	10 mm	8 mm	6 mm	2 kW
FLT-6012-3000W	4 in	20 ft	22 mm	10 mm	8 mm	6 mm	3 kW
FLT-6022-1000W	8 in	20 ft	10 mm	5 mm	3 mm	3 mm	1 kW
FLT-6022-1500W	8 in	20 ft	22 mm	10 mm	8 mm	6 mm	1.5 kW
FLT-6022-2000W	8 in	20 ft	22 mm	10 mm	8 mm	6 mm	2 kW
FLT-6022-3000W	8 in	20 ft	22 mm	10 mm	8 mm	6 mm	3 kW
FLT-6022-4000W	8 in	20 ft	22 mm	10 mm	8 mm	6 mm	4 kW
FLT-6022-6000W	8 in	20 ft	22 mm	10 mm	8 mm	6 mm	6 kW
FLT-6035-1000W	13 in	20 ft	10 mm	5 mm	3 mm	3 mm	1 kW
FLT-6035-1500W	13 in	20 ft	16 mm	6 mm	4 mm	3 mm	1.5 kW
FLT-6035-3000W	13 in	20 ft	22 mm	10 mm	8 mm	6 mm	3 kW
FLT-6035-4000W	13 in	20 ft	22 mm	10 mm	8 mm	6 mm	4 kW
FLT-6035-6000W	13 in	20 ft	30 mm	20 mm	14 mm	12 mm	6 kW
Equipped with Automatic Feeder							
FLU-6022-1000W	8 in	20 ft	10 mm	5 mm	3 mm	3 mm	1 kW
FLU-6022-1500W	8 in	20 ft	22 mm	10 mm	8 mm	6 mm	1.5 kW
FLU-6022-2000W	8 in	20 ft	22 mm	10 mm	8 mm	6 mm	2 kW
FLU-6022-4000W	8 in	20 ft	22 mm	10 mm	8 mm	6 mm	4 kW
FLU-6022-6000W	8 in	20 ft	22 mm	10 mm	8 mm	6 mm	6 kW

Specifications For All Models

Positioning accuracy of X/Y axes: ± 0.05 mm

Positioning repeatability of X/Y axes: ± 0.03 mm

Power supply: $\sim 3 \times 480$ V 60 Hz or other



+1 (419) 872-2364

sales@utubeonline.com